

### General Description

- Latest Trench Power AlphaMOS (αMOS LV) technology
- Very Low  $R_{DS(on)}$  at  $4.5V_{GS}$
- Low Gate Charge
- High Current Capability
- RoHS and Halogen-Free Compliant

### Application


- DC/DC Converters in Computing, Servers, and POL
- Isolated DC/DC Converters in Telecom and Industrial

### Product Summary

|                                  | Q1     | Q2     |
|----------------------------------|--------|--------|
| $V_{DS}$                         | 30V    | 30V    |
| $I_D$ (at $V_{GS}=10V$ )         | 58A    | 85A    |
| $R_{DS(on)}$ (at $V_{GS}=10V$ )  | <5.4mΩ | <1.5mΩ |
| $R_{DS(on)}$ (at $V_{GS}=4.5V$ ) | <8.5mΩ | <2.3mΩ |

100% UIS Tested

100% Rg Tested



### Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

| Parameter                                       | Symbol         | Max Q1                  | Max Q2   | Units            |   |
|---|----------------|-------------------------|----------|------------------|---|
| Drain-Source Voltage                            | $V_{DS}$       | 30                      |          | V                |   |
| Gate-Source Voltage                             | $V_{GS}$       | $\pm 20$                | $\pm 20$ | V                |   |
| Continuous Drain Current                        | $I_D$          | $T_C=25^\circ\text{C}$  | 58       | 85               | A |
|   |                | $T_C=100^\circ\text{C}$ | 36       | 66               |   |
| Pulsed Drain Current <sup>C</sup>               | $I_{DM}$       | 135                     | 340      |                  |   |
| Continuous Drain Current                        | $I_{DSM}$      | $T_A=25^\circ\text{C}$  | 24       | 42               | A |
|   |                | $T_A=70^\circ\text{C}$  | 19       | 33               |   |
| Avalanche Current <sup>C</sup>                  | $I_{AS}$       | 35                      | 65       | A                |   |
| Avalanche Energy $L=0.05\text{mH}$ <sup>C</sup> | $E_{AS}$       | 31                      | 106      | mJ               |   |
| $V_{DS}$ Spike                                  | $V_{SPIKE}$    | 36                      | 36       | V                |   |
| Power Dissipation <sup>B</sup>                  | $P_D$          | $T_C=25^\circ\text{C}$  | 31       | 78               | W |
|   |                | $T_C=100^\circ\text{C}$ | 12       | 31               |   |
| Power Dissipation <sup>A</sup>                  | $P_{DSM}$      | $T_A=25^\circ\text{C}$  | 5        | 4.1              | W |
|   |                | $T_A=70^\circ\text{C}$  | 3.2      | 2.6              |   |
| Junction and Storage Temperature Range          | $T_J, T_{STG}$ | -55 to 150              |          | $^\circ\text{C}$ |   |

### Thermal Characteristics

| Parameter                                  | Symbol          | Typ Q1 | Typ Q2 | Max Q1 | Max Q2 | Units              |
|--|-----------------|--------|--------|--------|--------|--------------------|
| Maximum Junction-to-Ambient <sup>A</sup>   | $R_{\theta JA}$ | 20     | 25     | 25     | 30     | $^\circ\text{C/W}$ |
| Maximum Junction-to-Ambient <sup>A,D</sup> |                 |        |        |        |        |                    |
| Maximum Junction-to-Case                   | $R_{\theta JC}$ | 3.3    | 1.2    | 4      | 1.6    | $^\circ\text{C/W}$ |

**Q1 Electrical Characteristics (T<sub>J</sub>=25°C unless otherwise noted)**

| Symbol                      | Parameter                             | Conditions   | Min | Typ  | Max    | Units |
|-----------------------------|---------------------------------------|--|-----|------|--------|-------|
| <b>STATIC PARAMETERS</b>    |                                       |  |     |      |        |       |
| BV <sub>DSS</sub>           | Drain-Source Breakdown Voltage        | I <sub>D</sub> =250μA, V <sub>GS</sub> =0V   | 30  |      |        | V     |
| I <sub>DSS</sub>            | Zero Gate Voltage Drain Current       | V <sub>DS</sub> =30V, V <sub>GS</sub> =0V<br>T <sub>J</sub> =55°C                          |     |      | 1<br>5 | μA    |
| I <sub>GSS</sub>            | Gate-Body leakage current             | V <sub>DS</sub> =0V, V <sub>GS</sub> = ±20V  |     |      | ±100   | nA    |
| V <sub>GS(th)</sub>         | Gate Threshold Voltage                | V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA                                   | 1.3 | 1.8  | 2.3    | V     |
| R <sub>DS(ON)</sub>         | Static Drain-Source On-Resistance     | V <sub>GS</sub> =10V, I <sub>D</sub> =20A<br>T <sub>J</sub> =125°C                         |     | 4.4  | 5.4    | mΩ    |
|                             |                                       | V <sub>GS</sub> =4.5V, I <sub>D</sub> =20A   |     | 6.8  | 8.3    |       |
| g <sub>FS</sub>             | Forward Transconductance              | V <sub>DS</sub> =5V, I <sub>D</sub> =20A   |     | 80   |        | S     |
| V <sub>SD</sub>             | Diode Forward Voltage                 | I <sub>S</sub> =1A, V <sub>GS</sub> =0V  |     | 0.7  | 1      | V     |
| I <sub>S</sub>              | Maximum Body-Diode Continuous Current |  |     |      | 35     | A     |
| <b>DYNAMIC PARAMETERS</b>   |                                       |  |     |      |        |       |
| C <sub>iss</sub>            | Input Capacitance                     |  |     | 1171 |        | pF    |
| C <sub>oss</sub>            | Output Capacitance                    | V <sub>GS</sub> =0V, V <sub>DS</sub> =15V, f=1MHz  |     | 284  |        | pF    |
| C <sub>rss</sub>            | Reverse Transfer Capacitance          |  |     | 59   |        | pF    |
| R <sub>g</sub>              | Gate resistance                       | V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, f=1MHz   | 0.3 | 0.6  | 0.9    | Ω     |
| <b>SWITCHING PARAMETERS</b> |                                       |  |     |      |        |       |
| Q <sub>g(10V)</sub>         | Total Gate Charge                     | V <sub>GS</sub> =10V, V <sub>DS</sub> =15V, I <sub>D</sub> =20A                            |     | 17   | 23     | nC    |
| Q <sub>g(4.5V)</sub>        | Total Gate Charge                     |  |     | 8    | 11     | nC    |
| Q <sub>gs</sub>             | Gate Source Charge                    |  |     | 4.7  |        | nC    |
| Q <sub>gd</sub>             | Gate Drain Charge                     |  |     | 2    |        | nC    |
| t <sub>D(on)</sub>          | Turn-On DelayTime                     | V <sub>GS</sub> =10V, V <sub>DS</sub> =15V, R <sub>L</sub> =0.75Ω,<br>R <sub>GEN</sub> =3Ω |     | 6.5  |        | ns    |
| t <sub>r</sub>              | Turn-On Rise Time                     |  |     | 15.5 |        | ns    |
| t <sub>D(off)</sub>         | Turn-Off DelayTime                    |  |     | 17   |        | ns    |
| t <sub>f</sub>              | Turn-Off Fall Time                    |  |     | 2.5  |        | ns    |
| t <sub>rr</sub>             | Body Diode Reverse Recovery Time      | I <sub>F</sub> =20A, dI/dt=500A/μs   |     | 12.3 |        | ns    |
| Q <sub>rr</sub>             | Body Diode Reverse Recovery Charge    | I <sub>F</sub> =20A, dI/dt=500A/μs   |     | 22.5 |        | nC    |

A. The value of R<sub>θJA</sub> is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with T<sub>A</sub> =25° C. The Power dissipation P<sub>DSM</sub> is based on R<sub>θJA</sub> t ≤ 10s and the maximum allowed junction temperature of 150° C. The value in any given application depends on the user's specific board design.

B. The power dissipation P<sub>D</sub> is based on T<sub>J(MAX)</sub>=150° C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature T<sub>J(MAX)</sub>=150° C. Ratings are based on low frequency and duty cycles to keep initial T<sub>J</sub> =25° C.

D. The R<sub>θJA</sub> is the sum of the thermal impedance from junction to case R<sub>θJC</sub> and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.


F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of T<sub>J(MAX)</sub>=150° C. The SOA curve provides a single pulse rating.

G. The maximum current rating is limited by package.


H. These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with T<sub>A</sub>=25° C.

COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.


**Q1-CHANNEL: TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**




**Figure 1: On-Region Characteristics (Note E)**




**Figure 2: Transfer Characteristics (Note E)**




**Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)**



**Figure 4: On-Resistance vs. Junction Temperature (Note E)**




**Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)**




**Figure 6: Body-Diode Characteristics (Note E)**


**Q1-CHANNEL: TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**




**Figure 7: Gate-Charge Characteristics**




**Figure 8: Capacitance Characteristics**



**Figure 9: Maximum Forward Biased Safe Operating Area (Note F)**



**Figure 10: Single Pulse Power Rating Junction-to-Case (Note F)**



**Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)**

**Q1-CHANNEL: TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**




Figure 12: Power De-rating (Note F)




Figure 13: Current De-rating (Note F)




Figure 14: Single Pulse Power Rating Junction-to-Ambient (Note H)




Figure 15: Normalized Maximum Transient Thermal Impedance (Note H)

**Q2 Electrical Characteristics (T<sub>J</sub>=25°C unless otherwise noted)**

| Symbol                      | Parameter  | Conditions   | Min | Typ  | Max        | Units |
|-----------------------------|--|--|-----|------|------------|-------|
| <b>STATIC PARAMETERS</b>    |  |  |     |      |            |       |
| BV <sub>DSS</sub>           | Drain-Source Breakdown Voltage                     | I <sub>D</sub> =10mA, V <sub>GS</sub> =0V  | 30  |      |            | V     |
| I <sub>DSS</sub>            | Zero Gate Voltage Drain Current                    | V <sub>DS</sub> =30V, V <sub>GS</sub> =0V<br>T <sub>J</sub> =55°C                          |     |      | 0.5<br>100 | mA    |
| I <sub>GSS</sub>            | Gate-Body leakage current                          | V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V   |     |      | ±100       | nA    |
| V <sub>GS(th)</sub>         | Gate Threshold Voltage                             | V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA                                   | 1.3 | 1.8  | 2.3        | V     |
| R <sub>DS(ON)</sub>         | Static Drain-Source On-Resistance                  | V <sub>GS</sub> =10V, I <sub>D</sub> =20A<br>T <sub>J</sub> =125°C                         |     | 1.2  | 1.5        | mΩ    |
|                             |  | V <sub>GS</sub> =4.5V, I <sub>D</sub> =20A   |     | 1.6  | 2          | mΩ    |
| g <sub>FS</sub>             | Forward Transconductance                           | V <sub>DS</sub> =5V, I <sub>D</sub> =20A   |     | 100  |            | S     |
| V <sub>SD</sub>             | Diode Forward Voltage                              | I <sub>S</sub> =1A, V <sub>GS</sub> =0V  |     | 0.46 | 0.6        | V     |
| I <sub>S</sub>              | Maximum Body-Diode Continuous Current <sup>G</sup> |  |     |      | 85         | A     |
| <b>DYNAMIC PARAMETERS</b>   |  |  |     |      |            |       |
| C <sub>iss</sub>            | Input Capacitance                                  | V <sub>GS</sub> =0V, V <sub>DS</sub> =15V, f=1MHz  |     | 3973 |            | pF    |
| C <sub>oss</sub>            | Output Capacitance                                 |  |     | 1100 |            | pF    |
| C <sub>rss</sub>            | Reverse Transfer Capacitance                       |  |     | 134  |            | pF    |
| R <sub>g</sub>              | Gate resistance                                    | V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, f=1MHz   | 0.3 | 0.65 | 1          | Ω     |
| <b>SWITCHING PARAMETERS</b> |  |  |     |      |            |       |
| Q <sub>g(10V)</sub>         | Total Gate Charge                                  | V <sub>GS</sub> =10V, V <sub>DS</sub> =15V, I <sub>D</sub> =20A                            |     | 60   | 85         | nC    |
| Q <sub>g(4.5V)</sub>        | Total Gate Charge                                  |  |     | 27   | 38         | nC    |
| Q <sub>gs</sub>             | Gate Source Charge                                 |  |     | 12   |            | nC    |
| Q <sub>gd</sub>             | Gate Drain Charge                                  |  |     | 10   |            | nC    |
| t <sub>D(on)</sub>          | Turn-On DelayTime                                  | V <sub>GS</sub> =10V, V <sub>DS</sub> =15V, R <sub>L</sub> =0.75Ω,<br>R <sub>GEN</sub> =3Ω |     | 11.5 |            | ns    |
| t <sub>r</sub>              | Turn-On Rise Time                                  |  |     | 16   |            | ns    |
| t <sub>D(off)</sub>         | Turn-Off DelayTime                                 |  |     | 38   |            | ns    |
| t <sub>f</sub>              | Turn-Off Fall Time                                 |  |     | 7    |            | ns    |
| t <sub>rr</sub>             | Body Diode Reverse Recovery Time                   | I <sub>F</sub> =20A, dI/dt=500A/μs   |     | 20.8 |            | ns    |
| Q <sub>rr</sub>             | Body Diode Reverse Recovery Charge                 | I <sub>F</sub> =20A, dI/dt=500A/μs   |     | 60   |            | nC    |

A. The value of R<sub>θJA</sub> is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with T<sub>A</sub> =25° C. The Power dissipation P<sub>DSM</sub> is based on R<sub>θJA</sub> t ≤ 10s and the maximum allowed junction temperature of 150° C. The value in any given application depends on the user's specific board design.

B. The power dissipation P<sub>D</sub> is based on T<sub>J(MAX)</sub>=150° C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature T<sub>J(MAX)</sub>=150° C. Ratings are based on low frequency and duty cycles to keep initial T<sub>J</sub> =25° C.

D. The R<sub>θJA</sub> is the sum of the thermal impedance from junction to case R<sub>θJC</sub> and case to ambient.


E. The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of T<sub>J(MAX)</sub>=150° C. The SOA curve provides a single pulse rating.


G. The maximum current rating is limited by package.

H. These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with T<sub>A</sub>=25° C.


COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.




**Fig 1: On-Region Characteristics (Note E)**




**Figure 2: Transfer Characteristics (Note E)**




**Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)**



**Figure 4: On-Resistance vs. Junction Temperature (Note E)**



**Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)**



**Figure 6: Body-Diode Characteristics (Note E)**




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note F)




Figure 10: Single Pulse Power Rating Junction-to-Case (Note F)




Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)






Figure 12: Power De-rating (Note F)




Figure 13: Current De-rating (Note F)




Figure 14: Single Pulse Power Rating Junction-to-Ambient (Note H)






Figure 15: Normalized Maximum Transient Thermal Impedance (Note H)


**Gate Charge Test Circuit & Waveform**



**Resistive Switching Test Circuit & Waveforms**



**Unclamped Inductive Switching (UIS) Test Circuit & Waveforms**



**Diode Recovery Test Circuit & Waveforms**

