



**ALPHA & OMEGA**  
SEMICONDUCTOR

**AOTF66811L**  
**80V N-Channel AlphaSGT2™**

### General Description

- Trench Power AlphaSGT2™ technology
- Low  $R_{DS(ON)}$  and optimized switching performance
- RoHS 2.0 and Halogen-Free Compliant


### Product Summary

$V_{DS}$	80V
$I_D$ (at $V_{GS}=10V$ )	80A
$R_{DS(ON)}$ (at $V_{GS}=10V$ )	< 3mΩ
$R_{DS(ON)}$ (at $V_{GS}=8V$ )	< 3.4mΩ

### Applications

- Industrial Application
- Telecom and Server Power Supply

100% UIS Tested  
100%  $R_g$  Tested



Orderable Part Number	Package Type	Form	Minimum Order Quantity
AOTF66811L	TO-220F	Tube	1000

**Absolute Maximum Ratings  $T_A=25^\circ C$  unless otherwise noted**

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	$V_{DS}$	80	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current <sup>G</sup>	$I_D$	80	A
$T_C=100^\circ C$		51	
Pulsed Drain Current <sup>C</sup>	$I_{DM}$	320	
Continuous Drain Current	$I_{DSM}$	39	A
$T_A=70^\circ C$		31	
Avalanche Current <sup>C</sup>	$I_{AS}$	75	A
Avalanche energy $L=0.1mH$ <sup>C</sup>	$E_{AS}$	281	mJ
Power Dissipation <sup>B</sup>	$P_D$	34	W
$T_C=100^\circ C$		14	
Power Dissipation <sup>A</sup>	$P_{DSM}$	8.3	W
$T_A=70^\circ C$		5.3	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	°C

### Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup>	$R_{QJA}$	10	15	°C/W
Maximum Junction-to-Ambient <sup>A,D</sup>		45	60	°C/W
Maximum Junction-to-Case	$R_{QJC}$	3	3.6	°C/W

**Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$BV_{DSS}$	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	80			V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS}=80\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$		1	5	$\mu\text{A}$
$I_{GSS}$	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm20\text{V}$			$\pm100$	nA
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	2.6	3.2	3.8	V
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}, I_D=20\text{A}$ $T_J=125^\circ\text{C}$		2.5	3	$\text{m}\Omega$
		$V_{GS}=8\text{V}, I_D=20\text{A}$		3.6	4.4	$\text{m}\Omega$
$g_{FS}$	Forward Transconductance	$V_{DS}=5\text{V}, I_D=20\text{A}$		90		S
$V_{SD}$	Diode Forward Voltage	$I_S=1\text{A}, V_{GS}=0\text{V}$		0.7	1	V
$I_S$	Maximum Body-Diode Continuous Current				40	A
<b>DYNAMIC PARAMETERS</b>						
$C_{iss}$	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=40\text{V}, f=1\text{MHz}$		5750		pF
$C_{oss}$	Output Capacitance			1580		pF
$C_{rss}$	Reverse Transfer Capacitance			30		pF
$R_g$	Gate resistance	$f=1\text{MHz}$	0.5	1.0	1.5	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g(10\text{V})$	Total Gate Charge	$V_{GS}=10\text{V}, V_{DS}=40\text{V}, I_D=20\text{A}$		77	110	nC
$Q_{gs}$	Gate Source Charge			21		nC
$Q_{gd}$	Gate Drain Charge			15		nC
$Q_{oss}$	Output Charge	$V_{GS}=0\text{V}, V_{DS}=40\text{V}$		112		nC
$t_{D(\text{on})}$	Turn-On DelayTime	$V_{GS}=10\text{V}, V_{DS}=40\text{V}, R_L=2.0\Omega, R_{\text{GEN}}=3\Omega$		19		ns
$t_r$	Turn-On Rise Time			7		ns
$t_{D(\text{off})}$	Turn-Off DelayTime			45		ns
$t_f$	Turn-Off Fall Time			10		ns
$t_{rr}$	Body Diode Reverse Recovery Time	$I_F=20\text{A}, di/dt=500\text{A}/\mu\text{s}$		35		ns
$Q_{rr}$	Body Diode Reverse Recovery Charge	$I_F=20\text{A}, di/dt=500\text{A}/\mu\text{s}$		175		nC

A. The value of  $R_{\text{JJA}}$  is measured, in a still air environment with  $T_A=25^\circ\text{C}$ . The Power dissipation  $P_{\text{DSM}}$  is based on  $R_{\text{JJA}} \leq 10\text{s}$  and the maximum allowed junction temperature of  $150^\circ\text{C}$ . The value in any given application depends on the user's specific board design, and the maximum temperature of  $150^\circ\text{C}$  may be used if the PCB allows it.

B. The power dissipation  $P_D$  is based on  $T_{J(\text{MAX})}=150^\circ\text{C}$ , using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Single pulse width limited by junction temperature  $T_{J(\text{MAX})}=150^\circ\text{C}$ .

D. The  $R_{\text{JJA}}$  is the sum of the thermal impedance from junction to case  $R_{\text{JJC}}$  and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using  $<300\mu\text{s}$  pulses, duty cycle 0.5% max.







F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of  $T_{J(\text{MAX})}=150^\circ\text{C}$ . The SOA curve provides a single pulse rating.






G. The maximum current rating is package limited.

H. These tests are performed, in a still air environment with  $T_A=25^\circ\text{C}$ .

APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO MAKE CHANGES TO PRODUCT SPECIFICATIONS WITHOUT NOTICE. IT IS THE RESPONSIBILITY OF THE CUSTOMER TO EVALUATE SUITABILITY OF THE PRODUCT FOR THEIR INTENDED APPLICATION. CUSTOMER SHALL COMPLY WITH APPLICABLE LEGAL REQUIREMENTS, INCLUDING ALL APPLICABLE EXPORT CONTROL RULES, REGULATIONS AND LIMITATIONS.

AOS' products are provided subject to AOS' terms and conditions of sale which are set forth at:  
[http://www.aosmd.com/terms\\_and\\_conditions\\_of\\_sale](http://www.aosmd.com/terms_and_conditions_of_sale)

**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**


**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**

**Figure 7: Gate-Charge Characteristics**

**Figure 8: Capacitance Characteristics**

**Figure 9: Maximum Forward Biased Safe Operating Area (Note F)**

**Figure 10: Single Pulse Power Rating Junction-to-Case (Note F)**

**Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)**






**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**

**Figure 12: Power De-rating (Note F)**

**Figure 13: Current De-rating (Note F)**

**Figure 14: Coss stored Energy**

**Figure 15: Single Pulse Power Rating  
Junction-to-Ambient (Note H)**

**Figure 16: Normalized Maximum Transient Thermal Impedance (Note H)**

Figure A: Gate Charge Test Circuit &amp; Waveforms




Figure B: Resistive Switching Test Circuit &amp; Waveforms




Figure C: Unclamped Inductive Switching (UIS) Test Circuit &amp; Waveforms




Figure D: Diode Recovery Test Circuit &amp; Waveforms

